



WEVER & DUCRÉ
LIGHTING

SOLID 1.0 LED

133365K9

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Jet Black + Gold

IP20

Interior

345 lm

LED

1800 K - 2850 K

CRI 95

4-step binning

OPTICAL

Beam angle 34°

PHYSICAL

Diameter 100 mm

Height 130 mm

0.65 kg

Tilt min 25°

Tilt max 25°

Rotation 355°

ELECTRICAL


DALI dim

220 - 240 V


Total connected power 7.7 W

PC1


Safety distance 0.3 m



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; adjustable; surface Jet Black + Gold; wet painted; matt smooth; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; DALI dim; light colour 1800 K - 2850 K; Binning initial 4 MacAdam; CRI 95; beam angle 34°; 355° rotatable and 25° tiltable; degree of protection IP20; PC1; power supply included; light source replaceable by an authorized professional; control gear replaceable by end-user;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

SOLID 1.0 LED

133365K9

CONE DIAGRAM

34°

h (m)	E0° (lx)	ø (m)
1	857	0.62
2	214	1.24
3	95	1.86
4	54	2.48
5	34	3.10

MOUNTING

Metal Spring clip

TYPE	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	59	7 3 2 4 0 2 0 3



Spring clip

TYPE	COLOUR	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	White	51	7 3 2 4 0 6 5 1
MR16 LED PAR16 max. 12W	Black	51	7 3 2 4 0 6 5 2
MR16 LED PAR16 max. 12W	Gold	51	7 3 2 4 0 9 4 0
MR16 LED PAR16 max. 12W	Grey	51	7 3 2 4 0 9 4 1
MR16 LED PAR16 max. 12W	Copper	51	7 3 2 4 0 9 4 2