Mayfair mini

5495

Design By Diego Fortunato

Portable version powered by a rechargeable battery. This can be moved exactly where needed, indoors or out. A push button in the base turns it on and off and controls dimming.

Model Sheet



Finish

- 37 Terra Red
  NCS S 4040-Y70R
- 38 Terra Dark
  test ral
- 23 Warm White
  NCS S 0502-Y50R
- 47 Green L1
  NCS S 4005-G80Y
- 25 Beige D1
  NCS S 4005-Y50R

LED temperature color	2700 K
Dimming	Touch sensor
Instalation type	Portable with battery
Materials	Shade: ABS Diffuser: PC- Polycarbonate Vertical tube: Steel Base: ABS
Light source	1 x LED PLATE 5V 2,5W A+
LED	CRI>90 223 lm 86 2700 K
Driver	Constant Voltage 100~240 V V 50~60 Hz HZ
Remarks	Rechargeable battery autonomy. 6 hours maximum intensity. 12 hours 50% intensity. 24 hours 25% intensity. F LED IP20 Bi-volt 50-60Hz
Application	Table Lamps
Packaging	1 Box 0.26 m x 0.25 m x 0.5 m Gross weigth 1.62 Net weigth 0.73 Vol. 0.0325

Lighting effect

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.

Photometric Data





Efficiency	86.077 lm/
Coordinate System	CG
Total Flux	223 lm
Maximum Value	365.58 cd/klm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com